



**CAPACITY & WEIGHT CHART BY BENDER MODEL**

	1	1A	2	3	4	6	8
<b>MAX RADIUS - SOLID</b>	2"	6"	9"	12"	12"	N/A	24"
<b>MAX RADIUS WITH QUIK-LOK</b>	2"	6"	7"	9"	9"	9"	N/A
<b>SOLID - ROUND (MILD STEEL)</b>	3/16"	5/16"	1/2"	5/8"	1"	5/8"	1"
<b>SOLID - SQUARE (MILD STEEL)</b>	1/8"	1/4"	3/8"	1/2"	3/4"		
<b>TUBING (MILD STEEL - 16 GAUGE WALL)</b>	5/16"	1/2"	3/4"	1"	1-1/4"	1-1/4"	1-1/2" - WITH SPECIAL SET-UP
<b>IPS TUBING</b>	-	-	3/8" IPS	1/2" IPS	1" IPS	3/4" IPS	1" IPS
<b>FLAT - EASY</b>	1/8" x 3/4"	3/16" x 1"	1/4" x 1.5"	1/4" x 2"	3/8" x 4"	1/4" x 2"	3/8" x 4"
<b>FLAT - HARD</b>	1/16" x 1/2"	1/8" x 1/2"	1/8" x 3/4"	1/8" x 1"	1/4" x 1"	1/4" x 1"	3/8" x 1"

	1	1A	2	3	4	6	8
<b>SHIPPING WEIGHT</b>	26 LBS	60 LBS	140 LBS	250 LBS	275 LBS	1,600 LBS	1,600 LBS
<b>STAND - NET WEIGHT</b>	69	69	69	69	69	-	-