

BENDER SPECIFICATIONS

	1	1A	2	3	4	6	8
MOUNTING PLATE DIAMETER	3"	6.5"	6.5"	9.5"	9.5"	—	14"
CENTER PIN DIAMETER	3/8"	1/2"	1"	1"	1"	1"	1"
NOSE HEIGHT	1/2"	3/4"	1"	1-1/2"	1-1/2"	1-1/2"	1-1/2"
TOOLING HEIGHT	1/2"	3/4"	PIN - 1" COLLAR - 1-1/2"	1-1/2"	1-1/2"	1-1/2"	1-1/2"
HOLDING PIN HOLE DIAMETER	1/4"	5/16"	1/2"	5/8"	3/4"	1/2"	3/4"

MACHINE CAPACITY (MILD STEEL)

	1	1A	2	3	4	6	8
MAX RADIUS - SOLID	2"	6"	9"	12"	12"	—	24"
MAX RADIUS - WITH QUIK-LOK	2"	6"	7"	9"	9"	9"	—
SOLID - ROUND	3/16"	5/16"	1/2"	5/8"	1"	5/8"	1"
ROUND TUBING (16G WALL)	5/16"	1/2"	3/4"	1"	1-1/4"	1-1/4"	1-1/2"
IPS TUBING	—	—	3/8" IPS	1/2" IPS	1" IPS	3/4" IPS	1" IPS
FLAT - EASY	1/8" x 3/4"	3/16" x 1"	1/4" x 1-1/2"	1/4" x 2"	3/8" x 4"	1/4" x 2"	3/8" x 4"
FLAT - HARD	1/16" x 1/2"	1/8" x 1/2"	1/8" x 3/4"	1/8" x 1"	1/4" x 1"	1/4" x 1"	3/8" x 1"

MACHINE WEIGHTS (LBS)

	1	1A	2	3	4	6	8
SHIPPING WEIGHT	26	60	145	255	280	1725	1725
STAND - NET WEIGHT	69	69	69	69	69	—	—